



BOSSWAY



TRUCK & BUS TIRES CATALOG

ABOUT YOUSHENG



Shandong Yousheng Tire Co., Ltd founded in September, 2019, is an enterprise specialized in high-performance tire development and manufacture.

Yousheng Tire covers an area of more than 800 mu and is located in Binhai economic development zone- Yangkou Industrial Park, Shouguang, Shandong. Yousheng Tire plans to achieve a production capacity of all steel radial tires of 2 million pcs for the first year.

Yousheng Tire focuses on market investigation and combines the product and market condition with advanced tire manufacturing and inspection equipment. Yousheng Tire owns professional management, technology and production team, well known scientific institution and perfect quality control system to develop best quality products.

Yousheng Tire takes "Industry benefits the society, devotion achieves the enterprise" as developing mission, and regards "Concentric cohesion creates first-class enterprise, Qualified product decides brand reputation" as enterprise goal. Yousheng Tire keeps on the innovation of technology, marketing, management, service and culture to develop and supply high quality products and to the customers of domestic and international market.

All positions, fit for medium and long distance, high speed on well paved road.

Excellent drive performance and handling performance.

Widened running surface and optimized grounding pressure, outstanding wear.



Medium and long distance, high speed on well paved road.


Four straight-line and wave pattern around the bottom groove improved the handling performance.

Low-heat generation, low noise, low-rolling resistance.



BF125

POSITION



SIZE	PLY	LI & SR	STANDARD WHEEL	RELATION PRESSURE	MAX LOAD	SECTION WIDTH	OVERALL DIAMETER	TREAD DEPTH
11.00R20	18	152/149L	8.00	930	3550/3250	293	1085	17
11R22.5	16	146/143M	8.25	830	3000/2725	279	1054	14.5
11R24.5	16	149/146M	8.25	830	3250/3000	200	1104	14
12R22.5	18	152/149M	9.00	930	3550/3250	300	1084	15
295/75R22.5	18	149/146J	9.00	830	3000/2725	298	1044	14.5
315/80R22.5	20	156/150M	9.00	850	4000/3350	312	1076	14.5

All positions, fit for medium and long distance, high speed on well paved road.


Excellent drive performance and handling performance.

Widened running surface and optimized grounding pressure, outstanding wear.



BA295

POSITION



SIZE	PLY	LI & SR	STANDARD WHEEL	RELATION PRESSURE	MAX LOAD	SECTION WIDTH	OVERALL DIAMETER	TREAD DEPTH
12.00R24	20	160/157 K	8.50	900	4500/4125	315	1226	14.5

Applied for low speed, mining , gravel etc. bad road conditions , all position of trucks.

Optimize the layout design of pattern block and groove angle provides excellent traction performance.

The design of tear resistant tread formula makes its tread life more tear resistant.



BD925

POSITION



SIZE	PLY	LI & SR	STANDARD WHEEL	RELATION PRESSURE	MAX LOAD	SECTION WIDTH	OVERALL DIAMETER	TREAD DEPTH
11.00R20	18	152/149F	8.00	930	3550/3250	293	1095	23
12.00R20	20	156/153F	8.50	900	4000/3650	315	1135	23.5

Medium and long distance, high speed on well paved road.


Four straight-line and wave pattern around the bottom groove improved the handling performance.

Low-heat generation, low noise, low-rolling resistance.



BF115

POSITION



SIZE	PLY	LI & SR	STANDARD WHEEL	RELATION PRESSURE	MAX LOAD	SECTION WIDTH	OVERALL DIAMETER	TREAD DEPTH
11R22.5	16	146/143M	8.25	830	3000/2725	279	1050	14.5

Mainly applicable to the drive shaft of vehicles with fixed load, long distance and high speed driving on good pavement


Deep groove and wide driving surface design, with superior high wear life.

Special block pattern design, with higher braking and driving.



BD515

POSITION



SIZE	PLY	LI & SR	STANDARD WHEEL	RELATION PRESSURE	MAX LOAD	SECTION WIDTH	OVERALL DIAMETER	TREAD DEPTH
12R22.5	18	152/149L	9.00	930	3550/3250	300	1084	19

Medium and long distance, high speed on well paved road.


The middle block design and the shoulder closed design ensure the grip of the tire and reduce the rolling resistance of the tire.

Special block pattern design, with higher driving force, excellent ground rolling resistance performance.



BD525

POSITION



SIZE	PLY	LI & SR	STANDARD WHEEL	RELATION PRESSURE	MAX LOAD	SECTION WIDTH	OVERALL DIAMETER	TREAD DEPTH
11R22.5	16	146/143L	8.25	830	3000/2725	210	1054	19.5
11R24.5	16	149/146L	8.25	830	3250/3000	210	1116	19.5
295/75R22.5	16	146/143L	9.00	830	3000/2725	298	1044	19.5